

## OKS 2670 / OKS 2671 Intensive Cleaner for the Food Processing Industry

---



### Description

OKS 2670 / OKS 2671 is a highly-effective cleaner on a solvent basis for use in the food processing industry.

### Applications

- Cleaning of bearings and machine parts
- Removal of aged and gummy oil and grease residues
- Dissolving of silicone and adhesive residues
- Preparation of surfaces for bonding

### Main fields of application

- Servicing, repair shops
- Food processing industry
- Livestock feed industry
- Pharmaceuticals industry

### Advantages and benefits

- High cleaning action through optimally matched mixture of active substances
- Rapid, residue-free evaporation of the cleaner
- NSF K1 K3 registered
- Good compatibility to common plastics such as polypropylene (PP), polycarbonate (PC), acrylonitrile-butadiene-styrene (ABS), polyethylene terephthalate (PET), polystyrene (PS), polyoxymethylene ((POM), polyvinyl chloride (PVC), polyethylene (PE), polytetrafluoroethylene (PTFE)
- OKS 2670 is suitable for use with the OKS Airspray system
- Also available as spray version OKS 2671

### Application tips

Wetting of the surfaces to be cleaned to excess. Cleaning is made even more effective if you simultaneously rub away at the surface with paper or cellulose cloths. If necessary, repeat the application at stubborn soiling. Subsequently allow to dry completely at room temperature. Dab away running cleaner with absorbent material and allow to evaporate in open air. Caution: Use only in well-ventilated rooms or in the open air. Limitations for use on elastomers and plastics, such as materials made of EPDM, neoprene, polyurethane, silicone, fluoroelastomers. We recommend therefore that you check the resistance before using the cleaner. Caution: Observe the specifications of the NSF when used in the food processing industry.

Our customer advice service will be pleased to help should you have any further questions.



# PRODUCT INFORMATION

## OKS 2670 / OKS 2671 Intensive Cleaner for the Food Processing Industry

### Technical data

	Standard	Conditions	Unit	Value
<b>Basis</b>				
Type				Solvent mixture
Flashing point		Active ingredient	°C	-15
<b>Application-specific data</b>				
Density	DIN EN ISO 3838	20°C	g/ml	0.78
Colour				Colourless
<b>Approvals</b>				
Food processing technology		OKS 2670		NSF K1, K3 Reg. No. 149997
Food processing technology		OKS 2671		NSF K1, K3 Reg. No. 149998

### Packaging

- 5 l canister
- 25 l canister
- 200 l drum
- 400 ml aerosol (OKS 2671)

### OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47  
82216 Maisach, Germany

Phone: +49 (0) 8142 3051 - 523 and 556

Fax: +49 (0) 8142 3051 - 923 and 956

info@oks-germany.com

[www.oks-germany.com](http://www.oks-germany.com)



Ein Unternehmen der  
Freudenberg Gruppe

The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress.  
® = Registered trademark

**Safety data sheet** for industrial and commercial users is available for downloading under [www.oks-germany.com](http://www.oks-germany.com).