




OKS 2101 - Product Information

Fields of Application:

Preservation of bare metal surfaces of all kinds, which are stored for longer periods and are subject to effects of weathering (industrial atmosphere, tropics, ocean). Protected parts retain their good appearance, as no surface discolouration occurs. Ideal stand by and storage protection for spare parts with possibility of direction installation. Can be welded without degreasing. Easily removable before coating (e.g. with OKS 2610/OKS 2611 Universal Cleaner).

OKS 2101 Protective Film for Metals, Spray



Advantages and Benefits:

Highly effective due to good film-forming properties. Excellent suited for producing dry to the touch, clean protective films. Outstanding corrosion and oxidation protection with lubricating effect. No degreasing prior to commissioning, as compatible with all lubricants. Waterproof and resistant to weathering. Suitable for all climate zones.

Application:

For optimum results clean surfaces, first mechanically and then with OKS 2610/OKS 2611 Universal Cleaner. The surfaces must be metallic bright and dry. Shake well before use. Spray from 20 - 30 cm distance to the prepared surface. Local excess should be avoided. Drying conditions acc. to the following technical data. For further questions please contact our technical department.

Additional Information:

Packaging (Article number):
- 500 ml Spray (02101005)

Version:
E-11.1/05

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark



OKS 2101 Protective Film for Metals, Spray

Technical Data

	Norm	Conditions	Unit	Value
Solid Lubricants				
Type				Synthetic wax
Solvents				
Type				Special boiling point gasoline
Flash point	DIN 51 755 (-2)	<65°C (<5°C)	°C	42
Additives				
Type				Corrosion protection
Film layer				
Optimum layer thickness	DIN 50 981/50 984	DIN 50 982-2	µm	40
Application temperature			°C	Room temperatur
Drying time		at 20°C	h	0,1
Surface coverage			m ² /Tin	7
Application Data				
Density	DIN EN ISO 3838	+20°C	g/ml	0,72
Colour				light-coloured
Service Temperatures				
Minimum service temperature			°C	-40
Maximum service temperature			°C	70
Corrosion Protection Tests				
Salt spray test	DIN 50 021	50 µm	h	> 1.000

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. © = Registered Trademark