


OKS 2650

BIologic Industrial Cleaner, water-based concentrate



Description

Alkaline cleaner on water basis for removing oily, greasy and sooty soiling.

Applications

- Cleaning of cooling devices, beverage and goods vending machines
- Cleaning of tiles, ceramics or natural stone
- Cleaning of construction machines and lorries, tarpaulins
- Cleaning of machine tools and workshop floors

Main fields of application

- Food processing technology
- Municipal services
- Workshops

Advantages and benefits

- NSF A1 registered
- Free of organic solvents and phosphates
- No vapours harmful to health during application
- Biodegradable
- Good separation behaviour
- Gentle to plastics, seals, rubber and sensitive metal surfaces
- Depending on the degree of soiling, can be diluted up to 1:10
- Suitable for use with high-pressure cleaners

Application tips

OKS 2650 is supplied ready for use. Additional dilution is usually not required. The cleaner has to be diluted more (1:10) to clean mirrors and glass surfaces. After spraying on, rub in mechanically and let it soak in for some minutes. Then rinse with clear water. Repeat the application at stubborn soiling. Caution: In the case of metal surfaces that can corrode when in contact with water dry the cleaned service thoroughly. OKS 2650 is not suitable for cleaning alkali-sensitive materials, acrylic and polycarbonate glass. We recommend therefore that you check the resistance of the surface before use.

Our customer advice service will be pleased to help should you have any further questions.



OKS 2650

BIologic Industrial Cleaner, water-based concentrate

Technical Data

| | Standard | Conditions | Unit | Value |
|----------------------------------|-----------------|------------|------------|----------------------------------|
| Basis | | | | |
| Type | | | | Non-ionic surfactants, silicates |
| pH value | | | | 11.0 (concentrate) |
| Dilution | | | with water | max. 1 : 10 |
| Application-specific data | | | | |
| Density | DIN EN ISO 3838 | 20°C | g/ml | 1.02 |
| Colour | | | | red |
| Approvals/Specifications | | | | |
| Food processing technology | | | | NSF A1 Reg. No. 129003 |

Packaging

- 500 ml bottle
- 5 l canister
- 25 l canister
- 200 l drum

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47
82216 Maisach, Germany

Phone: +49 (0) 8142 3051 - 523 and 556
Fax: +49 (0) 8142 3051 - 923 and 956

info@oks-germany.com
www.oks-germany.com

Ein Unternehmen der
Freudenberg Gruppe



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress.

® = Registered trademark

Safety data sheet for industrial and commercial users is available for downloading under www.oks-germany.com.