



OKS 2811 – Product Information

OKS 2811 Leak Detector Spray, Frost-proof to -15°C



Fields of Application:

Detection of leaks at pipes and containers under pressure, e.g. compressors, gas bottles, armatures, blocking valves, gas masks, autogenous and inert-gas welding equipment, Bunsen burners, valves, screwings of compressed-air pipes, etc. Suitable for compressed air, refrigerant media, acetylene, butane, propane, natural gas, city gas, oxygen, nitrogen, hydrogen, ammonia.

Advantages and Benefits:

Best suitability to detect even smallest leaks which are immediately visualized by the formation of bubbles at the leaking spot. Saves energy and warns of gas loss. Physiologically harmless, no corrosive effects. DVGW approved. Frost-proof to -15 °C. Non-flammable, therefore usable for the review of systems, containers and tubes with flammable gases.

Application:

Spray from distance of 30-50 cm onto the area to be checked, a formation of bubbles indicates a leakage. Clean with water after the application on plastic parts to prevent stress cracks. For additional questions please contact our technical department.

Additional Information:

Packaging (Article Number):
- 400 ml Spray (02811004)

Version:
E-01.1/13

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark



OKS 2811 Leak Detector Spray, Frost-proof to -15°C

Technical Data

	Norm	Conditions	Unit	Value
Base				
Type				Water
Admixture				
Additives				Corrosion protection active substances
Application Data				
Density	DIN EN ISO 3838	+20°C	g/ml	1,03
Colour				Colourless, clear
PH-value				7.0 – 8.0
Service Temperatures				
Minimum service temperature			°C	-15
Maximum service temperature			°C	50
Releases/Specifications				
DVGW	DIN EN 14291		Reg.-no.	DG-5170BL0103

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. © = Registered Trademark