




OKS 3740 - Product Information

Fields of Application:

Fully synthetic gear oil for the lubrication of all closed toothed gears, Liquid lubrication of chains, joints, guides, armatures, roller and plain bearings in the whole food and beverage industry as well as in breweries, when physiologically harmless lubricants are required.

OKS 3740

Gear Oil for the Food Industry



Advantages and Benefits:

Formulation acc. to the FDA guideline 21 CFR 178.3570. Registered by the NSF in category H1 under the number 135754 for the use in the food industry if an incidental contact is technically inevitable. Through optimum additivation against oxidation and aging economically extended operating times. Resistant to hot and cold water, steam, common disinfection and cleaning agents.

Application:

For optimum effect clean thoroughly the lubrication point first mechanically and then with OKS 2610/OKS 2611 Universal Cleaner. Before initial filling of gears remove corrosion protection agent. Fill gear in a way that the dipping teeth receive a sufficient amount of lubricant. Instructions of the gear and machine manufacturer have to be observed. Relubrication intervals and amount to be defined acc. to the service conditions. Mix with suitable lubricants only. For further questions please contact our Technical Department.

Additional Information:

Packaging (article number):

- 5 l canister (03740050)
- 25 l canister (03740062)

Version

E-04.1/13

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark



OKS 3740

Gear Oil for the Food Industry

Technical Data

	Norm	Conditions	Unit	Value
Classification	DIN 51 502			CLP HC 680
Base Oil				
Type				Synthetic oil mixture
Viscosity	DIN 51 562-1	40°C	mm ² /s	680
	DIN 51 562-1	100°C	mm ² /s	65
Viscosity index	DIN ISO 2909	method B		150
Viscosity class	DIN 51 519	DIN 51 562-1, 40°C	ISO VG- class	680
Pour point	DIN ISO 3016	3°C step	°C	<-25
Flash point	DIN ISO 2592	>79	°C	>200
Application Data				
Density	DIN EN ISO 3838	+20°C	g/ml	0,86
Colour				colourless
Service Temperatures				
Minimum service temperature			°C	-25
Maximum service temperature			°C	120
Gear Tests				
FZG damage grade	DIN 51 354 T2	A / 8,3 / 90	Force grade 0-12	> 12
FZG-wear	DIN 51 354 T2	A / 8,3 / 90	mg/kWh	< 0,2
Corrosion Protection Tests				
SKF-EMCOR	DIN EN ISO 2160	on copper, 24 h/100 °C	Corr.-Grade 1 - 3	1
Releases/Specifications				
Food industry				NSF H1 Reg.-no. 135754

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark