




## OKS 4100 - Product Information

### Fields of Application:

Grease lubrication of rolling and plain bearings subject to very heavy loading. Protection of bearings against harmful impurities. Protection against corrosion, maintenance of lubricating effect, even when exposed to large quantities of water.

### OKS 4100 MoS<sub>2</sub>-Extreme Pressure Grease



### Advantages and Benefits:

Excellently suited as a high-performance lubricating grease due to special EP properties and solid lubricants. The high base oil viscosity, with a stable soap basis even when exposed to water, results in a particular suitability for heavily loaded, slow-running bearings even with impact loading. Good emergency running properties due to solid lubricants.

### Application:

For best results clean the lubricating point carefully. Clean with solvents like OKS 2610/OKS 2611 Universal Cleaner. Remove the corrosion protection ahead of the initial filling. Fill the bearings in a way that all the functional surfaces for sure get the grease. Slow moving bearings(DN-value < 50.000) should be filled completely, normal moving bearings should be filled to 1/3 of the free inner housing space. Observe the instructions of the bearing or machine manufacturer. Relubrication with a grease gun on to the grease nipples or with an automatic lubrication system. Relubrication intervals and amount to be defined acc. to the service conditions. If the removal of the old grease is not possible the amount of grease has to be limited to avoid excess lubrication of the bearing. At longer relubrication intervals a complete exchange of the old grease is recommended. Only mix with appropriate lubricants. For additional questions please contact our Technical Department.

### Additional Information:

#### Packaging (Article number):

- 400 ml Cartridge (04100019)
- 1 kg Tin (04100034)
- 5 kg Hobbock (04100050)
- 25 kg Hobbock (04100062)
- 180 kg Drum (04100070)

#### Version

E-06.1/09

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. © = Registered Trademark



# OKS 4100 MoS<sub>2</sub>-Extreme Pressure Grease

## Technical Data

	Norm	Conditions	Unit	Value
Classification	DIN 51 502	DIN 51 825		KPF2K-20
<b>Base Oil</b>				
Type				Mineral oil
Viscosity	DIN 51 562-1	40°C	mm <sup>2</sup> /s	1020
	DIN 51 562-1	100°C	mm <sup>2</sup> /s	58
<b>Thickener</b>				
Type				Lithium-Calcium-Soap
Consistency	DIN 51 818	DIN ISO 2137	NLGI- class	2
Worked penetration	DIN ISO 2137	60 DH	0,1 mm	265 - 295
Drop point	IP 396		°C	> 180
<b>Additives</b>				
Solid lubrications, type				MoS <sub>2</sub> , Graphit
<b>Application Data</b>				
Density	DIN 51 757	+20°C	g/cm <sup>3</sup>	0,92
Colour				black
<b>Service Temperatures</b>				
Minimum service temperature	DIN 51 805	< 1.400 hPa	°C	-20
Maximum service temperature	DIN 51 821-2	F <sub>50</sub> (A/1500/600), 100h	°C	120
DN- value			mm/min	100.000
Water resistance	DIN 51 807-1		Grade	1 - 90
<b>Corrosion protection tests</b>				
SKF-EMCOR	DIN 51 802		Corr.-grade	0 and 0
<b>Wear protection tests</b>				
VBT- weld load (Four ball test rig)	DIN 51 350-4		N	> 4.000

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark