



## OKS 467 - Product Information

### Fields of Application:

For the lubrication of plastic/plastic and plastic/metal combinations e.g. single-serving taps in the food industry or for beverage can holders in the automotive industry. Silicone-free alternative for the lubrication of O-rings and sealings during assembly.



**OKS 467**  
**High Performance**  
**Grease for the Plastic**  
**Lubrication with PTFE**

### Advantages and Benefits:

Excellent adhesion on plastics with neutral behaviour to plastics and elastomers. Constant properties without drying, hardening or bleeding.

### Application:

For optimum effect clean thoroughly the lubrication point e.g. with OKS 2610/2611 Universal Cleaner. Apply an uniform thin layer of grease with brush, spatula etc. on the functional area. Avoid excess. Instructions of the bearing and machine manufacturer have to be observed. Due to a multitude of used polymers we strongly recommend to make tests in critical applications prior to the use. Relubrication intervals and amount to be defined acc. to the service conditions. Do only mix with suitable lubricants. For further questions please contact our technical department.



### Additional Information:

Packaging (article number):  
- 5 kg Hobbock (00467050)  
- 25 kg hobbock (00467062)

Version:  
E-01.1/10

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark



# OKS 467 High Performance Grease for the Plastic Lubrication with PTFE

## Technical Data

	Norm	Conditions	Unit	Value
<b>Base Oil</b>				
Type				synthetic oil
Viscosity		+40°C	mm <sup>2</sup> /s	1.500
<b>Thickener</b>				
Type				anorganic
Unworked penetration	DIN ISO 2137		0,1 mm	290 - 330
<b>Additives</b>				
Solid Lubricants				PTFE
<b>Application Data</b>				
Density	DIN EN ISO 3838	+20°C	g/ml	0,84
Colour				light-coloured
<b>Service Temperatures</b>				
Minimum service temperature			°C	-25
Maximum service temperature			°C	150

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. © = Registered Trademark