



OKS 641 - Product Information

Fields of Application:

Dismantling of all seized or sticky components or machine elements, e.g. door locks, hinges, bolts, bushings, cranks, linkages, valves, slide rails, cable pulls, shafts etc., at factories and workshops, automotive and hobby sectors. Lubrication of high-precision instruments, rolling bearings, measuring instruments, office and computer equipment, weapons etc., even at low temperatures. Displaces moisture on electrical contacts and protects against corrosion.

OKS 641 Maintenance Oil, Spray



Advantages and Benefits:

Highly effective due to ideal combination of mineral oils and additives with solvent. Broad range of uses in all maintenance applications. Displaces moisture, protects against corrosion, cleans, treats and lubricates, gets under rust.

Application:

Spray from a distance of 20 – 30 cm to the lubrication point to be completely wetted. To apply the product to bad accessible areas use the attached capillary tube. Let the product exhaust. Spray product on relevant parts to untighten heavy moving or rusty joints. Allow to work in for time corresponding to depth of penetration required. Repeat treatment if necessary. Slight hits on relevant places will ease the detachment procedure. Mix only with suitable lubricants. For additional questions please contact our technical department.



Additional Information:

Packaging (Article number):
- 500 ml Spray (00641005)

Version
E-10.2/07

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark



OKS 641 Maintenance Oil, Spray

Technical Data

	Norm	Conditions	Unit	Value
Base Oil				
Type				Mineral oil
Viscosity	DIN 51 562-1	+40°C	mm ² /s	3,1
Viscosity class	DIN 51 519	DIN 51 562-1, 40°C	ISO VG- class	3
Application Data				
Density	DIN EN ISO 3838	+20°C	g/ml	0,81
Colour				light brown
Service Temperatures				
Lower service temperature			°C	-50
Upper service temperature			°C	80
Application Data				
Salt spray test	DIN 50 021	sprayed	h	> 110

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. © = Registered Trademark