

Telefax: ++49(0)7041-963429



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Thread Locking Compound medium strength

Print date: 17.01.2017 Product code: 12-43 Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Thread Locking Compound medium strength

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives, sealants

Uses advised against

Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name: ITW LLC & Co. KG
Street: Mühlackerstrasse 149
Place: D-75417 Mühlacker
Telephone: ++49(0)7041-96340

e-mail: info@itwcp.de
Internet: www.itwcp.de
Responsible Department: Produktsicherheit

1.4. Emergency telephone ++49(0)7041-96340

number: Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents/container to Dispose of this material and its container to hazardous or

special waste collection point..

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Adhesives, sealants



according to Regulation (EC) No 1907/2006

Thread Locking Compound medium strength

Print date: 17.01.2017 Product code: 12-43 Page 2 of 7

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification according to Regulati	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
80-15-9	cumene hydroperoxide, alpha,alpha-dimethylbenzyl hydroperoxide				
	201-254-7	617-002-00-8			
	Org. Perox. E, Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, STOT RE 2, Skin Corr. 1B, Aquatic Chronic 2; H242 H331 H312 H302 H373 ** H314 H411				
128-37-0	Butylated hydroxytoluene (BHT)				
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410				
98-82-8	cumene				
	202-704-5	601-024-00-X			
	Flam. Liq. 3, Asp. Tox. 1, STOT SE 3, Aquatic Chronic 2; H226 H304 H335 H411				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off contaminated clothing.

After inhalation

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing. After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

If swallowed, immediately drink: Water. Rinse mouth immediately and drink plenty of water. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Foam. Extinguishing powder.

Unsuitable extinguishing media

Water with tenside additive. Water.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Nitrogen oxides (NOx). Carbon monoxide. Carbon dioxide (CO2).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures



according to Regulation (EC) No 1907/2006

Thread Locking Compound medium strength

Print date: 17.01.2017 Product code: 12-43 Page 3 of 7

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

This article doesn't contain dangerous substances or preparations intended to be released under normal or reasonably foreseeable conditions of use.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep/Store only in original container.

Advice on storage compatibility

Information about storage in one common storage facility: no restriction.

Further information on storage conditions

Keep container tightly closed. Keep in a cool, well-ventilated place. storage temperature: 10-20°C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
98-82-8	Cumene	25	125		TWA (8 h)	WEL
		50	250		STEL (15 min)	WEL

Additional advice on limit values

Does not contain substances above concentration limits fixing an occupational exposure limit.

8.2. Exposure controls





Protective and hygiene measures

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. No special precautionary measures are necessary.

ITW LLC & Co. KG



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Thread Locking Compound medium strength

Print date: 17.01.2017 Product code: 12-43 Page 4 of 7

Eye/face protection

Tightly sealed safety glasses.

Hand protection

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection

No special precautionary measures are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: blue
Odour: odourless

Test method

Changes in the physical state

Melting point:
Initial boiling point and boiling range:

Flash point:

not determined
not determined

> 100 °C

Explosive properties

not explosive.

Density (at 25 °C): 1,1 g/cm³
Water solubility: Immiscible
Viscosity / dynamic: 5000-10000 mPa·s

(at 25 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

Product is stable in the test system throughout the duration of the test.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on toxicological effects



according to Regulation (EC) No 1907/2006

Thread Locking Compound medium strength

Print date: 17.01.2017 Product code: 12-43 Page 5 of 7

Acute toxicity

CAS No	Chemical name						
	Exposure route	Dose		Species	Source		
80-15-9	cumene hydroperoxide, alpha,alpha-dimethylbenzyl hydroperoxide						
	oral	LD50	382 mg/kg	Rat	IUCLID		
	dermal	LD50	500 mg/kg	Rat	RTECS		
	inhalative (4 h) vapour	LC50	1,4 mg/l	Rat	IUCLID		
	inhalative aerosol	ATE	0,5 mg/l				
98-82-8	cumene						
	dermal	LD50	12300 mg/kg	Rabbit	IUCLID		
	inhalative (4 h) vapour	LC50	39 mg/l	Rat	RTECS		

Irritation and corrosivity

mild irritant.

Sensitising effects

not sensitising.

Carcinogenic/mutagenic/toxic effects for reproduction

No data available

STOT-repeated exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

Practical experience

Observations relevant to classification

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	
98-82-8	cumene						
	Acute fish toxicity	LC50	2,7 mg/l	96 h	Leuciscus idus		
	Acute algae toxicity	ErC50	2,6 mg/l	72 h	Selenastrum capricornutum		

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
98-82-8	cumene	3,66



ITW LLC & Co. KG

according to Regulation (EC) No 1907/2006

Thread Locking Compound medium strength

Print date: 17.01.2017 Product code: 12-43 Page 6 of 7

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

Further information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances

Classified as hazardous waste.

Waste disposal number of contaminated packaging

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); plastic packaging

Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

Other applicable information (land transport)

Not restricted

Inland waterways transport (ADN)

Other applicable information (inland waterways transport)

Not restricted

Marine transport (IMDG)

Other applicable information (marine transport)

Not restricted

Air transport (ICAO)

Other applicable information (air transport)

Not restricted

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Water contaminating class (D): 2 - water contaminating



according to Regulation (EC) No 1907/2006

Thread Locking Compound medium strength

Print date: 17.01.2017 Product code: 12-43 Page 7 of 7

SECTION 16: Other information

Relevant H and E	EUH statements (number and full text)
H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)