Telefax: ++49(0)7041-963429



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pipe Thread Sealant with PTFE

Print date: 20.01.2017 Product code: 15-72 Page 1 of 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Pipe Thread Sealant with PTFE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives, sealants

Uses advised against

Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name: ITW LLC & Co. KG
Street: Mühlackerstrasse 149
Place: D-75417 Mühlacker
Telephone: ++49(0)7041-96340

e-mail: info@itwcp.de
Internet: www.itwcp.de
Responsible Department: Produktsicherheit

1.4. Emergency telephone ++49(0)7041-96340

number: Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

According to EC directives or the corresponding national regulations the product does not have to be labelled. This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP].

2.2. Label elements

Additional advice on labelling

According to EC directives or the corresponding national regulations the product does not have to be labelled.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Adhesives, sealants

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
106-51-4	p-benzoquinone; quinone			<0,1 %
	203-405-2	606-013-00-3		
	Acute Tox. 3, Acute Tox. 3, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Aquatic Acute 1 (M-Factor = 10); H331 H301 H319 H335 H315 H400			


Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off contaminated clothing.





according to Regulation (EC) No 1907/2006

Pipe Thread Sealant with PTFE

Print date: 20.01.2017 Product code: 15-72 Page 2 of 6

After inhalation

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing. After contact with skin, wash immediately with plenty of water and soap.

After contact with eves

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

If swallowed, immediately drink: Water. Rinse mouth immediately and drink plenty of water. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Foam. Extinguishing powder.

Unsuitable extinguishing media

Water with tenside additive. Water.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Nitrogen oxides (NOx). Carbon monoxide. Carbon dioxide (CO2).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

This article doesn't contain dangerous substances or preparations intended to be released under normal or reasonably foreseeable conditions of use.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep/Store only in original container.



according to Regulation (EC) No 1907/2006

Pipe Thread Sealant with PTFE

Print date: 20.01.2017 Product code: 15-72 Page 3 of 6

Advice on storage compatibility

Information about storage in one common storage facility: no restriction.

Further information on storage conditions

Keep container tightly closed. Keep in a cool, well-ventilated place. storage temperature: 10-20°C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

Does not contain substances above concentration limits fixing an occupational exposure limit.

8.2. Exposure controls



Protective and hygiene measures

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. No special precautionary measures are necessary.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection

No special precautionary measures are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: whitish
Odour: odourless

Test method

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Flash point:

not determined
not determined

> 100 °C

Explosive properties

not explosive.

Density (at 25 °C):

Water solubility:

Viscosity / dynamic:
(at 25 °C)

1,00 g/cm³

Immiscible

15000-20000 mPa·s

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available



according to Regulation (EC) No 1907/2006

Pipe Thread Sealant with PTFE

Print date: 20.01.2017 Product code: 15-72 Page 4 of 6

10.2. Chemical stability

Product is stable in the test system throughout the duration of the test.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	
106-51-4	p-benzoquinone; quinone					
	oral	LD50	130 mg/kg	Rat	GESTIS	
	inhalative vapour	ATE	3 mg/l			
	inhalative aerosol	ATE	0,5 mg/l			

Irritation and corrosivity

mild irritant.

Sensitising effects

not sensitising.

Carcinogenic/mutagenic/toxic effects for reproduction

No data available

STOT-repeated exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

Practical experience

Observations relevant to classification

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

12.2. Persistence and degradability

No data available



according to Regulation (EC) No 1907/2006

Pipe Thread Sealant with PTFE

Print date: 20.01.2017 Product code: 15-72 Page 5 of 6

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-51-4	p-benzoquinone; quinone	0,19

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

Further information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances

Classified as hazardous waste.

Waste disposal number of contaminated packaging

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); plastic packaging

Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

Other applicable information (land transport)

Not restricted

Inland waterways transport (ADN)

Other applicable information (inland waterways transport)

Not restricted

Marine transport (IMDG)

Other applicable information (marine transport)

Not restricted

Air transport (ICAO)

Other applicable information (air transport)

Not restricted



according to Regulation (EC) No 1907/2006

Pipe Thread Sealant with PTFE

Print date: 20.01.2017 Product code: 15-72 Page 6 of 6

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)